NSN 5935-01-242-3586

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-242-3586 **Thread Class:** 2a and 2b **Thread Direction:** Left-hand and right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.860 inches **Overall Diameter:** 3.381 inches **Environmental Protection:** Corrosion resistant and vibration resistant and shock resistant and explosion proof **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 48-53 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 23.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1250.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Internally threaded shell **End Application:** Surveillance information processing center an/tsq-10 (v) 4 Thready Qty Per Inch (tpi): 16 and 10 **Thread Size:** 2.875 inches and 3.000 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-242-3586

Electrical Plug Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.037 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Uns and double stub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0