

View Online at <https://aerobasegroup.com/nsn/5935-01-242-3589>

Body Style:

Right angle type

Overall Length:

6.500 inches

Overall Width:

0.400 inches

Body Height:

0.580 inches

Unthreaded Mounting Hole Diameter:

Between 0.057 inches and 0.077 inches

Distance Between Mounting Facility Centers:

Between 6.195 inches and 6.205 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Guide pin/socket

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Nickel single mating end single contact grouping and gold single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment Specification:

Qq-n-290 federal specification 1st treatment response single mating end single contact grouping and mil-g-45204, type 2 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Guide Design And Location:

D shape pin right-hand at 3 o'clock

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Chromate

Shell Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Shell Material Specification:

Qq-a-200/8 federal specification single material response

Insert Material Specification:

Mil-p-20693, type 1 military specification single material response single mating end

Included Contact Quantity:

120 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.120 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.