

View Online at <https://aerobasegroup.com/nsn/5935-01-242-6027>

Body Style:

Straight shape, external coupling

Overall Length:

1.215 inches

Overall Diameter:

Between 1.235 inches and 1.266 inches

Distance From Mounting Shoulder To Front Face:

Between 0.658 inches and 0.707 inches

Mounting Facility Thickness:

Between 0.062 inches and 0.187 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Ajaa 12-8 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

10.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

200.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Included Contact Type:

Round pin single mating end single contact grouping

Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

96906-ms3474 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26482 spec.