NSN 5935-01-243-2936

Overall Length:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-243-2936

| 1.320 inches |
|---|
| Overall Height: |
| 1.234 inches |
| Overall Width: |
| 1.234 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 0.969 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.969 inches |
| Distance From Mounting Shoulder To Front Face: |
| 0.431 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 16-26 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 10.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 200.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 250.0 single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |

NSN 5935-01-243-2936

Included Contact Type:

Electrical Receptacle Connector - Page 2 of 2



| Round socket single mating end single contact grouping |
|--|
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material: |
| Gold |
| Test Data Document: |
| 81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 96906-ms3122 government standard |
| Shelf Life: |

Unit Of Measure:

Demilitarization: No

N/a

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26482 spec.