Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-243-3425

Body Style:
Right angle type
Overall Length:
1.460 inches
Overall Height:
0.680 inches
Overall Width:
0.410 inches
Unthreaded Mounting Hole Diameter:
0.096 inches
Distance Between Mounting Facility Centers:
1.060 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
End Application:
Piloted aircraft countermeasures maintenance and or test assemblies an/alm 233 se
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Gold single mating end single contact grouping Insert Material:
Gold single mating end single contact grouping Insert Material: Plastic polyester single mating end
Gold single mating end single contact grouping Insert Material: Plastic polyester single mating end Contact Surface Treatment Specification:
Gold single mating end single contact groupingInsert Material:Plastic polyester single mating endContact Surface Treatment Specification:Mil-g-45204 military specification single treatment response single mating end single contact grouping
Gold single mating end single contact groupingInsert Material:Plastic polyester single mating endContact Surface Treatment Specification:Mil-g-45204 military specification single treatment response single mating end single contact groupingTerminal Type:
Gold single mating end single contact groupingInsert Material:Plastic polyester single mating endContact Surface Treatment Specification:Mil-g-45204 military specification single treatment response single mating end single contact groupingTerminal Type:Pin single mating end single contact grouping
Gold single mating end single contact groupingInsert Material:Plastic polyester single mating endContact Surface Treatment Specification:Mil-g-45204 military specification single treatment response single mating end single contact groupingTerminal Type:Pin single mating end single contact groupingIncluded Contact Quantity:
Gold single mating end single contact groupingInsert Material:Plastic polyester single mating endContact Surface Treatment Specification:Mil-g-45204 military specification single treatment response single mating end single contact groupingTerminal Type:Pin single mating end single contact groupingIncluded Contact Quantity:28 single mating end single contact grouping
Gold single mating end single contact groupingInsert Material:Plastic polyester single mating endContact Surface Treatment Specification:Mil-g-45204 military specification single treatment response single mating end single contact groupingTerminal Type:Pin single mating end single contact groupingIncluded Contact Quantity:28 single mating end single contact groupingIncluded Contact Type:
Gold single mating end single contact groupingInsert Material:Plastic polyester single mating endContact Surface Treatment Specification:Mil-g-45204 military specification single treatment response single mating end single contact groupingTerminal Type:Pin single mating end single contact groupingIncluded Contact Quantity:28 single mating end single contact groupingIncluded Contact Type:Round pin single mating end single contact grouping
Gold single mating end single contact groupingInsert Material:Plastic polyester single mating endContact Surface Treatment Specification:Mil-g-45204 military specification single treatment response single mating end single contact groupingTerminal Type:Pin single mating end single contact groupingIncluded Contact Quantity:28 single mating end single contact groupingIncluded Contact Type:



Precious Material And Weight:

0.028 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.