## NSN 5935-01-243-3429

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-243-3429

Body Style:
Straight shape
Overall Length:
2.713 inches
Overall Width:
0.250 inches
Distance Between Mounting Facility Centers:
2.400 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and mil-c-14500 military specification 2nd
treatment response single mating end single contact grouping
Criticality Code Justification:
Feat

### **Terminal Type:**

Wire wrap single mating end single contact grouping

### **Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end single contact grouping or qq-b-613 federal specification single material response single mating end single contact grouping

### **Guide Design And Location:**

Hexagon shape female post left-hand at 9 oclock and hexagon shape female post right-hand at 9 oclock

#### **Insert Material Specification:**

Mil-m-14 military specification single material response single mating end

#### **Included Contact Quantity:**

41 single mating end single contact grouping

# NSN 5935-01-243-3429

Electrical Receptacle Connector - Page 2 of 2



# **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** Mtg stud is 0.191 in. Lg **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.041 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.