

View Online at <https://aerobasegroup.com/nsn/5935-01-243-4414>

Body Style:

Straight shape w/flange

Bushing Diameter:

2.062 inches

Mounting Hole Circle Radius:

1.125 inches

Overall Diameter:

2.875 inches

Environmental Protection:

Heat resistant and salt water resistant

Unthreaded Mounting Hole Diameter:

0.195 inches

Distance From Mounting Shoulder To Rear Face:

2.187 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

3 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

30.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

277.0 single mating end all contact groupings

Polarization Method:

Contact

Connector Locking Method:

Contact twistlock

Terminal Location:

Side single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Terminal Type:

Screw single mating end all contact groupings

Included Contact Quantity:

2 single mating end 2nd contact grouping

Included Contact Type:

Curved pin w/outside lip single mating end 1st contact grouping

Test Data Document:

81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81348-w-c-596/106 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0