## NSN 5935-01-243-6215

**Body Style:** 

Straight shape, external coupling

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-243-6215

Overall Length:
0.634 inches
Overall Height:
0.954 inches
Overall Width:
0.954 inches
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.130 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.719 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.719 inches
Distance From Mounting Shoulder To Front Face:
Between 0.317 inches and 0.322 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
40456 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
End Application:
1430-01-087-6338 engagement control
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping

## NSN 5935-01-243-6215

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Included Contact Quantity:
5 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.025 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms27499 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.