NSN 5935-01-243-6220

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-243-6220

view Online at https://acrobasegroup.com/hish/0333-01-243-0220
Body Style:
Straight shape, external coupling
Overall Length:
1.125 inches
Bushing Diameter:
0.406 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.562 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.562 inches
Distance From Mounting Shoulder To Front Face:
0.625 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Tnc single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
End Application:
2 generation vortac (2gvortac)
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Beryllium single mating end single contact grouping and copper single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic tetrafluoroethylene single mating end
Terminal Type:
Solder stud single mating end single contact grouping
Shell Material:

Copper alloy

NSN 5935-01-243-6220

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:

Gold and silver

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A039b0