Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-243-6788

# Body Style:

Straight shape

#### **Overall Length:**

2.180 inches

# **Overall Width:**

0.240 inches

### **Environmental Protection:**

Corrosion resistant and shock resistant and vibration resistant

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

### Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

### Connector Locking Method:

Friction

### **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

### **Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

### **Included Contact Quantity:**

40 single mating end single contact grouping

### Included Contact Type:

Flat socket single mating end single contact grouping

### Precious Material And Location:

Contact surfaces gold

### **Precious Material And Weight:**

0.040 gold grains, troy

### **Precious Material:**

Gold

## Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

No

# NSN 5935-01-243-6788

Electrical Plug Connector - Page 2 of 2



**Fiig:** A039b0

Mil-std (military Standard):

Mil-g-45204 spec.