## NSN 5935-01-243-6794

Receptacle Dummy Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-243-6794 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.003 inches **Overall Height:** Between 1.698 inches and 1.738 inches **Overall Width:** Between 1.698 inches and 1.738 inches **Environmental Protection:** Salt water resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.130 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.281 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.281 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 50.0 and 160.0 and 190.0 and 225.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 10 **Thread Size:** 1.500 inches **Shell Material:** Aluminum alloy **Shell Surface Treatment:** 

Shell Surface Treatment

Cadmium and nickel

**Shell Surface Treatment Specification:** 

Qq-p-416, type 2, class 3 federal specification 1st treatment response

## NSN 5935-01-243-6794

Receptacle Dummy Connector - Page 2 of 2



## **Test Data Document:**

81349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread	Series	Desi	iana	tor:
IIIICaa	OCI ICS	003	gua	LOI .

Double stub

**Specification Data:** 

81349-mil-c-28840/7 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0