

View Online at <https://aerobasegroup.com/nsn/5935-01-243-8374>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.234 inches

Overall Diameter:

0.984 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

13089 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Thread Length:

0.219 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.562 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074 military specification single treatment response

Included Contact Quantity:

13 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Heavier nickel plating required for emi/rfi protection

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.013 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.