## NSN 5935-01-244-1113

**Included Contact Quantity:** 

3 single mating end single contact grouping

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-244-1113

Body Style:	
Straight shape, external coupling	
Overall Length:	
5.033 inches	
Overall Diameter:	
1.812 inches	
Environmental Protection:	
Weather resistant and watertight and chemical resistant and corrosion resistant and dust resistant and shock	resistant
Cable Entrance Diameter:	
Between 0.250 inches and 0.625 inches	
Distance From Mounting Shoulder To Front Face:	
4.116 inches	
Mating End Quantity:	
1	
Contact Maximum Current Rating In Amps:	
30.0 single mating end single contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
480.0 single mating end single contact grouping	
Contact Maximum Frequency Rating:	
0.4 kilohertz single mating end single contact grouping	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
0.0	
Shell Type:	
Solid	
Connector Locking Method:	
Bayonet slot	
Connector Cable Strain Relief Method:	
Cable clamp	
Contact Material:	
Copper single mating end single contact grouping	
Insert Material:	
Plastic diallyl phthalate single mating end	
Terminal Type:	
Solder well single mating end single contact grouping	
Shell Material:	
Aluminum	
Shell Surface Treatment:	
Anodize	

## NSN 5935-01-244-1113

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Type:
----------	---------	-------

Round socket single mating end single contact grouping

**Special Features:** 

Furnished items - clamping nut

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0