

View Online at <https://aerobasegroup.com/nsn/5935-01-244-1114>

Body Style:

Straight shape, external coupling

Overall Length:

5.033 inches

Overall Diameter:

1.812 inches

Environmental Protection:

Weather resistant and watertight and chemical resistant and corrosion resistant and dust resistant and shock resistant

Cable Entrance Diameter:

Between 0.625 inches and 0.875 inches

Distance From Mounting Shoulder To Front Face:

4.116 inches

Mating End Quantity:

1

Contact Maximum Current Rating In Amps:

30.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

480.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

0.4 kilohertz single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet slot

Connector Cable Strain Relief Method:

Cable clamp

Contact Material:

Copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum

Shell Surface Treatment:

Anodize

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Furnished items - clamping nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0