Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-244-1119

Body Style:
Straight shape
Overall Length:
1.265 inches
Overall Height:
1.158 inches
Overall Width:
Between 4.300 inches and 4.330 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock resistant and thermal shock resistant
Unthreaded Mounting Hole Diameter:
0.197 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.562 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 3.870 inches and 3.880 inches
Distance From Mounting Shoulder To Front Face:
Between 0.615 inches and 0.630 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
101 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
2 polarization posts and mating end
Shell Type:
Solid
Connector Locking Method:
Friction
End Application:
5841-01-070-3859 radar, surveillance
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:

Plastic single mating end

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification: Mil-g-45204 military specification 1st treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Contact Material Specification:** Qq-c-533 federal specification single material response single mating end single contact grouping **Guide Design And Location:** Hexagon shape male post left-hand top at 6 oclock and hexagon shape male post right-hand bottom at 6 oclock **Shell Material:** Aluminum alloy a380.0 **Shell Surface Treatment:** Nickel **Shell Surface Treatment Specification:** Mil-c-26074, class 3 military specification single treatment response **Shell Material Specification:** Qq-a-591 federal specification single material response **Included Contact Quantity:** 101 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.101 gold grains, troy **Precious Material:** Gold Shelf Life: N/a

Unit Of Measure:

Demilitarization:

Mil-g-45204 spec.

Mil-std (military Standard):

--

No Fiig: A039b0