

View Online at <https://aerobasegroup.com/nsn/5935-01-244-1780>

**Body Style:**

Right angle type

**Overall Length:**

3.540 inches

**Overall Height:**

0.580 inches

**Environmental Protection:**

Humidity resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.075 inches and 0.078 inches

**Distance Between Mounting Facility Centers:**

3.340 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic polyamide single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Contact Material Specification:**

Qq-b-613, comp 2, 1/2 hard federal specification single material response single mating end single contact grouping

**Guide Design And Location:**

D shape pin right-hand at 5 oclock

**Shell Material:**

Aluminum alloy 6063 or aluminum alloy 6061

**Shell Surface Treatment:**

Chromate

**Shell Surface Treatment Specification:**

Mil-c-5541 military specification single treatment response

**Shell Material Specification:**

Qq-a-200/9 federal specification single material response or qq-a-200/8 federal specification single material response

**Insert Material Specification:**

L-p-410 federal specification single material response single mating end or mil-m-20693, type 1 military specification single material response single mating end

**Included Contact Quantity:**

60 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.060 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.