NSN 5935-01-244-2316

Guide Design And Location:

D shape socket right-hand at 7 oclock

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-244-2316

Body Style:
Straight type
Overall Length:
9.050 inches
Overall Height:
0.632 inches
Overall Width:
0.500 inches
Environmental Protection:
Vibration resistant and shock resistant and corrosion resistant and humidity resistant
Unthreaded Mounting Hole Diameter:
0.136 inches
Distance Between Mounting Facility Centers:
8.800 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Guide pin/socket
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polyamide single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federa
specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-c-533 federal specification single material response single mating end single contact grouping

NSN 5935-01-244-2316

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Chromate
Shell Surface Treatment Specification:
Mil-c-5541, cl 1a military specification single treatment response
Shell Material Specification:
Qq-a-200/8, t6 federal specification single material response
Insert Material Specification:
Mil-p-20693, type 1 military specification single material response single mating end
Included Contact Quantity:
150 single mating end single contact grouping
Included Contact Type:
Spring pincers single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.150 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.