

View Online at <https://aerobasegroup.com/nsn/5935-01-244-6924>

Body Style:

Straight edge type w/mounting flange

Overall Length:

4.290 inches

Overall Height:

0.680 inches

Overall Width:

0.343 inches

Environmental Protection:

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.142 inches

Distance Between Mounting Facility Centers:

4.030 inches

Board Accommodated Length:

3.600 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.070 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Tin single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Glass fiber single mating end and plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdc-f military specification all material responses single mating end

Included Contact Quantity:

44 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.