NSN 5935-01-244-7612

Right-hand and right-hand and right-hand

Contact Surface Treatment Specification:

treatment response single mating end single contact grouping

Thread Class: 2a and 2b and 2a Thread Direction:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-244-7612

Body Style:
Straight shape
Overall Length:
0.700 inches
Overall Height:
0.610 inches
Overall Width:
0.210 inches
Distance Between Mounting Facility Centers:
0.482 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
5 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56 and 56 and 56
Thread Size:
0.086 inches and 0.086 inches and 0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end and glass fiber single mating end

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd

NSN 5935-01-244-7612

Electrical Receptacle Connector - Page 2 of 2



Terminal Type: Pin single mating end single contact grouping **Insert Material Specification:** Mil-m-14, type sdg-f military specification all material responses single mating end **Unable To Decode:** Unable to decode and unable to decode **Included Contact Quantity:** 5 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Special Features:** Jackscrew type-female and location-right handandjackscrew type-male and location-left hand **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.005 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc and unc and unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.