Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-244-8312



## Thread Class:

2a

**Thread Direction:** 

Right-hand

#### Body Style:

Straight shape, internal coupling

### **Overall Length:**

0.766 inches

#### **Overall Diameter:**

1.156 inches

#### Threaded Device Type:

Back shell

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

14-15 single mating end

## **Contact Removability:**

Removable single mating end all contact groupings

#### Polarization Method:

Keyway or multiple keyway

#### Insert Position In Deg:

21.0

## Shell Type:

Solid

## **Connector Locking Method:**

Bayonet latch

## Thready Qty Per Inch (tpi):

20

## Thread Size:

0.812 inches

## **Terminal Location:**

Back single mating end all contact groupings

## **Contact Material:**

Copper alloy single mating end all contact groupings

## **Contact Surface Treatment:**

Gold single mating end all contact groupings

## Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end all contact groupings

## **Terminal Type:**

Crimp single mating end all contact groupings

## Shell Material:

Aluminum alloy

# NSN 5935-01-244-8312

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074 military specification single treatment response

## Included Contact Quantity:

14 single mating end 2nd contact grouping

## Included Contact Type:

Round pin single mating end all contact groupings

## **Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:** 

0.019 gold grains, troy

Precious Material:

Gold

#### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unef

Specification Data: 96906-ms27473 government standard Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.