NSN 5935-01-244-9467

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-244-9467

Body Style: Right angle type **Overall Length:** 0.720 inches **Overall Width:** 0.549 inches **Body Height:** 0.214 inches **Environmental Protection:** Corrosion resistant and shock resistant and vibration resistant **Mating End Quantity: Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Connector Locking Method:** Friction **End Application:** 6625-01-216-5858 radiac set, trainer **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Glass fiber single mating end and plastic polyamide single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification 1st treatment response single mating end single contact grouping **Terminal Type:** Tab, solder lug single mating end single contact grouping **Included Contact Quantity:** 6 single mating end single contact grouping **Included Contact Type:** Flat pin single mating end single contact grouping **Precious Material And Location:**

Contact surfaces gold

Precious Material And Weight:

0.006 gold grains, troy

NSN 5935-01-244-9467

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.