## NSN 5935-01-245-0754

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-245-0754

Thread Direction: Right-hand Body Style: Straight shape, internal coupling Overall Length: 34.16 millimeters Overall Diameter: 46.64 millimeters Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 23-55 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 110.0 and 250.0 Shell Type: Solid Connector Locking Method: Detent Thread Size:
Body Style: Straight shape, internal coupling Overall Length: 34.16 millimeters Overall Diameter: 46.64 millimeters Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 23-55 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 110.0 and 250.0 Shell Type: Solid Connector Locking Method: Detent
Straight shape, internal coupling  Overall Length:  34.16 millimeters  Overall Diameter:  46.64 millimeters  Threaded Device Type: Back shell  Mating End Quantity:  1  Contact Position Arrangement Style: 23-55 single mating end  Contact Removability: Removable single mating end single contact grouping  Polarization Method: Keyway or multiple keyway  Insert Position In Deg:  110.0 and 250.0  Shell Type: Solid  Connector Locking Method: Detent
Overall Length:  34.16 millimeters  Overall Diameter:  46.64 millimeters  Threaded Device Type: Back shell  Mating End Quantity:  1  Contact Position Arrangement Style: 23-55 single mating end  Contact Removability: Removable single mating end single contact grouping  Polarization Method: Keyway or multiple keyway  Insert Position In Deg:  110.0 and 250.0  Shell Type: Solid  Connector Locking Method: Detent
34.16 millimeters  Overall Diameter: 46.64 millimeters  Threaded Device Type: Back shell  Mating End Quantity: 1  Contact Position Arrangement Style: 23-55 single mating end  Contact Removability: Removable single mating end single contact grouping  Polarization Method: Keyway or multiple keyway  Insert Position In Deg: 110.0 and 250.0  Shell Type: Solid  Connector Locking Method: Detent
Overall Diameter: 46.64 millimeters Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 23-55 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 110.0 and 250.0 Shell Type: Solid Connector Locking Method: Detent
46.64 millimeters  Threaded Device Type: Back shell  Mating End Quantity:  1  Contact Position Arrangement Style: 23-55 single mating end  Contact Removability: Removable single mating end single contact grouping  Polarization Method: Keyway or multiple keyway  Insert Position In Deg:  110.0 and 250.0  Shell Type: Solid  Connector Locking Method: Detent
Threaded Device Type: Back shell  Mating End Quantity:  1  Contact Position Arrangement Style: 23-55 single mating end  Contact Removability: Removable single mating end single contact grouping  Polarization Method: Keyway or multiple keyway  Insert Position In Deg: 110.0 and 250.0  Shell Type: Solid  Connector Locking Method: Detent
Back shell  Mating End Quantity:  1  Contact Position Arrangement Style: 23-55 single mating end  Contact Removability: Removable single mating end single contact grouping  Polarization Method: Keyway or multiple keyway  Insert Position In Deg: 110.0 and 250.0  Shell Type: Solid  Connector Locking Method: Detent
Mating End Quantity:  1 Contact Position Arrangement Style: 23-55 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 110.0 and 250.0 Shell Type: Solid Connector Locking Method: Detent
Contact Position Arrangement Style:  23-55 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 110.0 and 250.0 Shell Type: Solid Connector Locking Method: Detent
Contact Position Arrangement Style:  23-55 single mating end  Contact Removability:  Removable single mating end single contact grouping  Polarization Method:  Keyway or multiple keyway  Insert Position In Deg:  110.0 and 250.0  Shell Type:  Solid  Connector Locking Method:  Detent
23-55 single mating end  Contact Removability:  Removable single mating end single contact grouping  Polarization Method:  Keyway or multiple keyway  Insert Position In Deg:  110.0 and 250.0  Shell Type:  Solid  Connector Locking Method:  Detent
Contact Removability: Removable single mating end single contact grouping  Polarization Method: Keyway or multiple keyway Insert Position In Deg: 110.0 and 250.0  Shell Type: Solid Connector Locking Method: Detent
Removable single mating end single contact grouping  Polarization Method:  Keyway or multiple keyway  Insert Position In Deg:  110.0 and 250.0  Shell Type:  Solid  Connector Locking Method:  Detent
Polarization Method: Keyway or multiple keyway Insert Position In Deg: 110.0 and 250.0 Shell Type: Solid Connector Locking Method: Detent
Keyway or multiple keyway  Insert Position In Deg:  110.0 and 250.0  Shell Type:  Solid  Connector Locking Method:  Detent
Insert Position In Deg:  110.0 and 250.0  Shell Type:  Solid  Connector Locking Method:  Detent
110.0 and 250.0  Shell Type: Solid  Connector Locking Method: Detent
Shell Type: Solid Connector Locking Method: Detent
Solid  Connector Locking Method:  Detent
Connector Locking Method:  Detent
Detent
Thread Size:
34.0 millimeters
Thread Pitch In Millimeters:
1.00
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel

## NSN 5935-01-245-0754

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment Specification:
Mil-c-26074, cl 3 or 4, grade b military specification single treatment response
Thread Tolerance Class:
6g external
Included Contact Quantity:
55 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.055 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Iso m
Specification Data:
81349-dod-c-38999/49 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: