

NSN 5935-01-245-2024 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-245-2024 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Right angle type **Overall Length:** 2.350 inches **Overall Height:** 0.572 inches **Overall Width:** 0.250 inches **Environmental Protection:** Shock resistant and vibration resistant and corrosion resistant and humidity resistant **Unthreaded Mounting Hole Diameter:** 0.107 inches **Distance Between Mounting Facility Centers:** 2.100 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket

Thread Length:

0.130 inches

Thready Qty Per Inch (tpi):

56

**Thread Size:** 

0.086 inches

**Terminal Location:** 

Side single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

# NSN 5935-01-245-2024

Electrical Receptacle Connector - Page 2 of 2



#### **Insert Material:**

Glass fiber single mating end and plastic polyphenylene single mating end

#### **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1, gr c military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping

### **Terminal Type:**

Pin single mating end single contact grouping

### **Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-c-530 federal specification single material response single mating end single contact grouping or qq-w-321 federal specification single material response single mating end single contact grouping

# **Insert Material Specification:**

Mil-p-46174, class 40, grade e military specification all material responses single mating end

#### **Unable To Decode:**

Unable to decode and unable to decode

#### **Included Contact Quantity:**

30 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Special Features:**

Jackscrew type-male and location-right handandjackscrew type-female and location-left hand

# **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.030 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.