

View Online at <https://aerobasegroup.com/nsn/5935-01-245-2026>

**Thread Class:**

2b and 2b and 2a

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Rectangular shape

**Overall Length:**

Between 2.302 inches and 2.322 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 1.992 inches and 2.008 inches

**Overall Height:**

1.269 inches

**Overall Width:**

Between 0.740 inches and 0.760 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.121 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.463 inches and 0.473 inches

**Threaded Device Type:**

Coupling facility and mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

42 single mating end

**Contact Removability:**

Removable single mating end 1st contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end 1st contact grouping

**Polarization Method:**

Jackscrew

**Connector Locking Method:**

Post jacksocket

**Thready Qty Per Inch (tpi):**

32 and 32 and 40

**Thread Size:**

0.138 inches and 0.138 inches and 0.112 inches

**Terminal Location:**

Back single mating end 1st contact grouping

**Contact Material:**

Copper alloy single mating end 1st contact grouping

**Contact Surface Treatment:**

Gold single mating end 1st contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end and glass fiber single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end 1st contact grouping

**Terminal Type:**

Tab, solder lug single mating end 1st contact grouping

**Contact Material Specification:**

Astm b 140 assn standard single material response single mating end 1st contact grouping

**Insert Material Specification:**

Mil-m-14, ty gdi-30f or ty sd-6f military specification all material responses single mating end

**Unable To Decode:**

Unable to decode and unable to decode

**Included Contact Quantity:**

10 single mating end 1st contact grouping

**Included Contact Type:**

Round socket single mating end 1st contact grouping

**Special Features:**

Jackscrew type-female and location-right hand and jackscrew type-female and location-left hand

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc and unc and unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.