NSN 5935-01-245-3394

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-245-3394

Body Style:
Right angle type
Overall Length:
2.850 inches
Overall Width:
0.250 inches
Body Height:
0.525 inches
Environmental Protection:
Vibration resistant and shock resistant and salt water resistant and humidity resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end 1st contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end 1st contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Terminal Location:
Side single mating end 1st contact grouping
Contact Material:
Copper alloy single mating end 1st contact grouping
Contact Surface Treatment:
Gold single mating end 1st contact grouping
Insert Material:
Plastic polyphenylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end 1st contact grouping
Criticality Code Justification:
Feat
Terminal Type:
Pin single mating end 1st contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end 1st contact grouping or qq-c-533 federal specification single
material response single mating end 1st contact grouping

Insert Material Specification:

Mil-m-24519 military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

NSN 5935-01-245-3394

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 49 single mating end 1st contact grouping **Included Contact Type:** Round socket single mating end 1st contact grouping **Special Features:** Polarizing pin in contact position 35 **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.049 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.