Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-245-4671

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Right angle type

Overall Length:

2.550 inches

Overall Width:

0.250 inches

Body Height:

0.400 inches

Environmental Protection:

Vibration resistant and shock resistant and salt water resistant and humidity resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Glass fiber single mating end and plastic polyphenylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping



Pin	single mating end single contact grouping
Cor	ntact Material Specification:
Qq-	c-530 federal specification single material response single mating end single contact groupir
Inse	ert Material Specification:
Mil-	p-46174, cl 40, gr e military specification all material responses single mating end
Una	able To Decode:
Una	able to decode and unable to decode
Incl	uded Contact Quantity:
44 s	single mating end single contact grouping
Incl	uded Contact Type:
Rou	and pin single mating end single contact grouping
Spe	ecial Features:
Jacl	kscrew type-male and location-right handandjackscrew type-female and location-left hand
Pre	cious Material And Location:
Con	ntact surfaces gold
Pre	cious Material And Weight:
0.04	14 gold grains, troy
Pre	cious Material:
Golo	d
Thre	ead Series Designator:
Unc	
She	elf Life:
N/a	
Unit	t Of Measure:
Den	nilitarization:
No	
Fiig	r.
A03	9960
Mil-	std (military Standard):
Mil-	g-45204 spec.