

View Online at <https://aerobasegroup.com/nsn/5935-01-245-9362>

Overall Length:

0.530 inches

Overall Width:

0.360 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock proof and vibration proof

Cable Entrance Diameter:

0.200 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

6 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Mating end

Connector Locking Method:

Friction

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Included Contact Quantity:

6 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Corner's 3 and 4 on case are beveled at a 45 degree angle

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.030 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.