

View Online at <https://aerobasegroup.com/nsn/5935-01-246-2780>

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.150 inches

**Overall Diameter:**

0.560 inches

**Environmental Protection:**

Waterproof

**Cable Entrance Diameter:**

0.255 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Twin-x single mating end

**Contact Removability:**

Removable single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

100.0 single mating end all contact groupings

**Contact Maximum Frequency Rating:**

100.0 megahertz single mating end all contact groupings

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Connector Cable Strain Relief Method:**

Compression nut

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

90.0 single mating end all contact groupings

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Silver single mating end all contact groupings

**Insert Material:**

Plastic polytetrafluoroethylene single mating end

**Terminal Type:**

Crimp single mating end all contact groupings

**Shell Material:**

Copper alloy

**Included Contact Quantity:**

1 single mating end 2nd contact grouping

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.010 silver grains, troy

**Precious Material:**

Silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0