Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-246-2793

Body Style:
Straight shape
Overall Length:
2.320 inches
Overall Height:
Between 3.095 inches and 3.125 inches
Overall Width:
Between 1.985 inches and 2.015 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.118 inches and 0.122 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
2.783 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.437 inches
Distance From Mounting Shoulder To Front Face:
Between 0.764 inches and 0.768 inches
Mating End Quantity:
2
Contact Position Arrangement Style:
32 1st mating end
Contact Removability:
Removable all mating ends all contact groupings
Polarization Method:
3 polarization posts
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back all mating ends all contact groupings
Contact Material:
Copper alloy all mating ends all contact groupings
Contact Surface Treatment:
Gold all mating ends all contact groupings
Insert Material:
Plastic diallyl phthalate all mating ends or plastic epoxy all mating ends or plastic phenolic all mating ends
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response all mating ends all contact groupings
Terminal Type:
Crimp all mating ends all contact groupings



## Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

# Shell Surface Treatment Specification:

Qq-p-416 federal specification all treatment responses

# **Shell Material Specification:**

Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal

specification single material response

### **Insert Material Specification:**

Mil-m-14 military specification single material response all mating ends or 1288 bx mfr ref single material response all mating ends

# **Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:** 

0.174 gold grains, troy

### **Precious Material:**

Gold

# **Test Data Document:**

81349-mil-c-81659 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

# environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

81349-mil-c-81659/33 government specification

#### Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

# Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.