

View Online at <https://aerobasegroup.com/nsn/5935-01-246-2799>

**Body Style:**

Straight edge type w/card guide

**Overall Length:**

7.084 inches

**Overall Width:**

0.390 inches

**Body Height:**

1.185 inches

**Environmental Protection:**

Cold resistant and heat resistant and vibration resistant and salt water resistant and moisture resistant

**Board Accommodated Length:**

6.924 inches single board

**Board Accommodated Width:**

Between 0.057 inches and 0.086 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic polyester single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, ty ii, cl 1 military specification 1st treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Insert Material Specification:**

Mil-m-24519, ty gpt-30f military specification single material response single mating end

**Unable To Decode:**

Unable to decode and unable to decode and unable to decode

**Included Contact Quantity:**

112 single mating end single contact grouping

**Included Contact Type:**

Bifurcated spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.112 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.