

View Online at <https://aerobasegroup.com/nsn/5935-01-246-2799>

Body Style:

Straight edge type w/card guide

Overall Length:

7.084 inches

Overall Width:

0.390 inches

Body Height:

1.185 inches

Environmental Protection:

Cold resistant and heat resistant and vibration resistant and salt water resistant and moisture resistant

Board Accommodated Length:

6.924 inches single board

Board Accommodated Width:

Between 0.057 inches and 0.086 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyester single mating end

Contact Surface Treatment Specification:

Mil-g-45204, ty ii, cl 1 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Insert Material Specification:

Mil-m-24519, ty gpt-30f military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode and unable to decode

Included Contact Quantity:

112 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.112 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.