NSN 5935-01-246-4531

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-246-4531 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Angle shape w/cable clamp **Overall Diameter:** 1.734 inches **Body Angle In Deg:** 90.0 **Cable Entrance Diameter:** 0.594 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Nk-12 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 15.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring **Connector Cable Strain Relief Method:** Cable clamp **Distance From Centerline To Connector End:** 1.547 inches **Distance From Centerline To Cable End:** 1.562 inches Thready Qty Per Inch (tpi): 6 **Thread Size:** 1.562 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-246-4531

A039b0

Electrical Plug Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Plastic single mating end or plastic phenolic single mating end
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
12 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.012 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Special acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: