Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-246-5474

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape

Overall Length:

3.130 inches

Overall Height:

0.690 inches

Overall Width:

0.370 inches

Distance Between Mounting Facility Centers:

2.800 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

74 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

32 and 32 and 40

Thread Size:

0.138 inches and 0.138 inches and 0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd

treatment response single mating end single contact grouping



,	Terminal Type:
	Solder well single mating end single contact grouping
	Contact Material Specification:
	Qq-b-750 federal specification single material response single mating end single contact grouping
	Insert Material Specification:
	Mil-m-14, ty mdg military specification single material response single mating end
	Unable To Decode:
	Unable to decode and unable to decode
	Included Contact Quantity:
	74 single mating end single contact grouping
	Included Contact Type:
	Round socket single mating end single contact grouping
	Special Features:
	Jackscrew type-male and location-left handandjackscrew type-female and location-right hand
	Precious Material And Location:
	Contact surfaces gold
	Precious Material And Weight:
	0.074 gold grains, troy
	Precious Material:
	Gold
,	Thread Series Designator:
	Unc and unc and unc
	Shelf Life:
	N/a
	Unit Of Measure:
	Demilitarization:
	No
	Fiig:
	A039b0
	Mil-std (military Standard):
	Mil-g-45204 spec.