NSN 5935-01-246-9828

Thread Class:

2a

Electrical Receptacle Connector - Page 1 of 2

treatment response single mating end all contact groupings



View Online at https://aerobasegroup.com/nsn/5935-01-246-9828

Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
2.750 inches
Overall Height:
Between 1.594 inches and 1.656 inches
Overall Width:
Between 1.594 inches and 1.656 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.245 inches and 1.255 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.245 inches and 1.255 inches
Distance From Mounting Shoulder To Front Face:
Between 0.750 inches and 0.781 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
22-23 single mating end
Contact Maximum Current Rating In Amps:
41.0 single mating end all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
900.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
1250.0 single mating end all contact groupings
Shell Type:
Solid
Thready Qty Per Inch (tpi):
18
Thread Size:
1.375 inches
Terminal Location:
Back single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings or silver single mating end all contact groupings
Contact Surface Treatment Specification:
Qq-s-365 federal specification 1st treatment response single mating end all contact groupings and mil-g-45204 military specification 2nd

NSN 5935-01-246-9828

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type ii, class 3 federal specification single treatment response
Included Contact Quantity:
7 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material:
Silver and gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.