## NSN 5935-01-247-1206



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-247-1206 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, w/ or w/o cover **Overall Length:** 4.250 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 3.500 inches **Overall Height:** 4.880 inches **Overall Width:** 4.250 inches **Environmental Protection:** Humidity resistant and fungus resistant and corrosion resistant and weather resistant Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 3.500 inches **Threaded Device Type:** Coupling facility and mounting hole **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 4 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 60.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 22.5 Shell Type: Solid **Connector Locking Method:** 

18

Internally threaded shell Thready Qty Per Inch (tpi):

## NSN 5935-01-247-1206

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
0.312 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Crimp and solder single mating end single contact grouping
Shell Material:
Aluminum
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0