

View Online at <https://aerobasegroup.com/nsn/5935-01-247-1211>

**Thread Class:**

2a and 2a and 2b

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.289 inches

**Overall Height:**

1.125 inches

**Overall Width:**

1.125 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.123 inches and 0.138 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.906 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.906 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.815 inches and 0.820 inches

**Threaded Device Type:**

Back shell and mounting hole

**Mating End Quantity:**

12

**Contact Position Arrangement Style:**

13-35 single mating end

**Polarization Method:**

Keyway or multiple keyway and key, multiple key groove

**Insert Position In Deg:**

340.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**End Application:**

5821-01-092-4907 reciver-transmitter, radio

**Thready Qty Per Inch (tpi):**

24 and 24 and 40

**Thread Size:**

0.688 inches and 1.000 inches

**Shell Material:**

Aluminum alloy or zinc

**Shell Surface Treatment:**

Cadmium and chromate and zinc

**Shell Surface Treatment Specification:**

Qq-p-416 ty ii, cl 3 federal specification single treatment response

**Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef and unef and unef

**Specification Data:**

96906-ms27656 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-38999 spec.