

View Online at <https://aerobasegroup.com/nsn/5935-01-247-3392>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Wall type

Overall Height:

1.750 inches

Overall Width:

1.125 inches

Body Length:

2.875 inches

Environmental Protection:

Heat resistant and salt water resistant

Distance Between Mounting Facility Centers:

3.281 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

4 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

20.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

120.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

208.0 single mating end all contact groupings

Connector Locking Method:

Contact twistlock

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Terminal Location:

Side single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Terminal Type:

Screw single mating end all contact groupings

Included Contact Quantity:

3 single mating end 2nd contact grouping

Included Contact Type:

Curved socket w/outside lip single mating end 2nd contact grouping

Test Data Document:

81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81348-w-c-596/59 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0