NSN 5935-01-247-5134

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-247-5134

| Body Style: |
|---|
| Right angle type |
| Overall Length: |
| 3.540 inches |
| Overall Width: |
| 0.579 inches |
| Environmental Protection: |
| Humidity resistant and salt water resistant and thermal shock resistant and vibration resistant |
| Unthreaded Mounting Hole Diameter: |
| Between 0.075 inches and 0.078 inches |
| Distance Between Mounting Facility Centers: |
| 3.340 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 2 rows of contacts non-inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Polarization Method: |
| Guide pin/socket |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Friction |
| Terminal Location: |
| Side single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Insert Material: |
| Plastic polyamide single mating end |
| Contact Surface Treatment Specification: |
| $\label{eq:milder} \mbox{Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal}$ |
| specification 2nd treatment response single mating end single contact grouping |
| Criticality Code Justification: |
| Feat |
| Terminal Type: |
| Pin single mating end single contact grouping |

Qq-b-613, comp 2 federal specification single material response single mating end single contact grouping

Shell Material:

Aluminum alloy 6063 or aluminum alloy 6061

Contact Material Specification:

NSN 5935-01-247-5134

Electrical Receptacle Connector - Page 2 of 2



| Shell Surface Treatment: |
|---|
| Chromate |
| Shell Surface Treatment Specification: |
| Mil-c-5541 military specification single treatment response |
| Shell Material Specification: |
| Qq-a-200/9 federal specification 1st material response or qq-a-200/8 federal specification 2nd material response |
| Insert Material Specification: |
| L-p-410 federal specification all material responses single mating end or mil-m-20693, type 1 military specification all material responses |
| single mating end |
| Included Contact Quantity: |
| 60 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Special Features: |
| D-shaped guides used for polarization, clocking position is unknown |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.060 gold grains, troy |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |

Demilitarization: No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.