NSN 5935-01-247-5135

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-247-5135

Body Style: Right angle type **Overall Length:** 3.540 inches **Overall Width:** 0.579 inches **Environmental Protection:** Humidity resistant and salt water resistant and thermal shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.075 inches and 0.078 inches **Distance Between Mounting Facility Centers:** 3.340 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Guide pin/socket Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic polyamide single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping **Criticality Code Justification:** Feat **Terminal Type:** Pin single mating end single contact grouping

Qq-b-613, comp 2 federal specification single material response single mating end single contact grouping

Shell Material:

Aluminum alloy 6063 or aluminum alloy 6061

Contact Material Specification:

NSN 5935-01-247-5135

Electrical Receptacle Connector - Page 2 of 2



material responses

Shell Surface Treatment:	
Chromate	
Shell Surface Treatment Specification:	
Mil-c-5541 military specification single treatment response	
Shell Material Specification:	
Qq-a-200/9 federal specification 1st material response or qq-a-200/8 feder	fication 2nd material response
Insert Material Specification:	
L-p-410 federal specification all material responses single mating end or mil-m-206	693, type 1 military specification all
single mating end	
Included Contact Quantity:	
60 single mating end single contact grouping	
Included Contact Type:	
Round pin single mating end single contact grouping	
Special Features:	
D-shaped guides used for polarization, clocking position is unknown	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.060 gold grains, troy	
Precious Material:	
Gold	
Shelf Life:	
N/a	
Unit Of Measure:	

Demilitarization:

No **Fiig:**

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.