Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-247-9412



# Thread Class:

2a

**Thread Direction:** 

Right-hand

# Body Style:

Straight shape, internal coupling w/backshell

## **Overall Length:**

1.234 inches

#### **Overall Diameter:**

1.406 inches

#### Threaded Device Type:

Back shell

## Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

17-26 single mating end

## **Contact Removability:**

Removable single mating end single contact grouping

#### Polarization Method:

Keyway or multiple keyway

## Insert Position In Deg:

0.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet latch

# Thready Qty Per Inch (tpi):

20

# Thread Size:

0.938 inches

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

# **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

# **Criticality Code Justification:**

Feat

# **Terminal Type:**

Crimp single mating end single contact grouping

# **NSN 5935-01-247-9412** Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Included Contact Quantity:
26 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Heavier cadmium plating required for corrosion protection
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.026 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.