## NSN 5935-01-247-9414

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-247-9414 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling strain relief **Overall Length:** 2.937 inches **Overall Height:** 2.750 inches **Overall Width:** 2.750 inches **Environmental Protection:** Cold resistant and heat resistant and corrosion resistant and dust resistant and chemical resistant and humidity resistant and moisture resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.219 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 2.093 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:** 2.093 inches **Distance From Mounting Shoulder To Front Face:** 1.609 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 20-337 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 60.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1250.0 single mating end single contact grouping **Polarization Method:** 

0.0

Shell Type:

Keyway or multiple keyway Insert Position In Deg:

Solid

## NSN 5935-01-247-9414

Electrical Receptacle Connector - Page 2 of 2



Connector Locking Method:
Externally threaded shell
Connector Cable Strain Relief Method:
Compression nut
Thready Qty Per Inch (tpi):
10
Thread Size:
2.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Anodize
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.025 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Special acme
Special acine
Shelf Life:
Shelf Life:
Shelf Life: N/a
Shelf Life: N/a
Shelf Life: N/a Unit Of Measure:
Shelf Life: N/a Unit Of Measure: Demilitarization: