NSN 5935-01-247-9414

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-247-9414 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling strain relief **Overall Length:** 2.937 inches **Overall Height:** 2.750 inches **Overall Width:** 2.750 inches **Environmental Protection:** Cold resistant and heat resistant and corrosion resistant and dust resistant and chemical resistant and humidity resistant and moisture resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.219 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 2.093 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.093 inches **Distance From Mounting Shoulder To Front Face:** 1.609 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 20-337 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 60.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1250.0 single mating end single contact grouping **Polarization Method:**

0.0

Shell Type:

Keyway or multiple keyway Insert Position In Deg:

Solid

NSN 5935-01-247-9414

Electrical Receptacle Connector - Page 2 of 2



| Connector Locking Method: |
|--|
| Externally threaded shell |
| Connector Cable Strain Relief Method: |
| Compression nut |
| Thready Qty Per Inch (tpi): |
| 10 |
| Thread Size: |
| 2.500 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Silver single mating end single contact grouping |
| Insert Material: |
| Rubber single mating end |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum |
| Shell Surface Treatment: |
| Anodize |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces silver |
| Precious Material And Weight: |
| 0.025 silver grains, troy |
| Precious Material: |
| Silver |
| Thread Series Designator: |
| Special acme |
| Special acine |
| Shelf Life: |
| |
| Shelf Life: |
| Shelf Life: N/a |
| Shelf Life: N/a |
| Shelf Life: N/a Unit Of Measure: |
| Shelf Life: N/a Unit Of Measure: Demilitarization: |