Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-248-1289

#### **Body Style:**

Right angle type

#### **Overall Length:**

3.540 inches

## **Overall Width:**

0.579 inches

#### **Environmental Protection:**

Humidity resistant and salt water resistant and thermal shock resistant and vibration resistant

#### **Unthreaded Mounting Hole Diameter:**

Between 0.075 inches and 0.078 inches

#### **Distance Between Mounting Facility Centers:**

3.340 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### Contact Removability:

Nonremovable single mating end single contact grouping

#### Polarization Method:

Guide pin/socket

## Shell Type:

Solid

#### **Connector Locking Method:**

Friction

Terminal Location:

Side single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic polyamide single mating end

#### **Contact Surface Treatment Specification:**

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal

specification 2nd treatment response single mating end single contact grouping

#### Criticality Code Justification:

Feat

#### Terminal Type:

Pin single mating end single contact grouping

#### **Contact Material Specification:**

Qq-b-613, comp 2 federal specification single material response single mating end single contact grouping

#### Shell Material:

Aluminum alloy 6063 or aluminum alloy 6061

# NSN 5935-01-248-1289

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:

Chromate

Shell Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

## Shell Material Specification:

Qq-a-200/9 federal specification 1st material response or qq-a-200/8 federal specification 2nd material response

#### **Insert Material Specification:**

L-p-410 federal specification all material responses single mating end or mil-m-20693, type 1 military specification all material responses

single mating end

#### **Included Contact Quantity:**

60 single mating end single contact grouping

#### Included Contact Type:

Round pin single mating end single contact grouping

#### **Special Features:**

D-shaped guides used for polarization, clocking position is unknown

## Precious Material And Location:

Contact surfaces gold

## **Precious Material And Weight:**

0.060 gold grains, troy

## **Precious Material:**

Gold

## Shelf Life:

N/a

## Unit Of Measure:

\_\_\_

# Demilitarization:

No

#### Fiig:

A039b0

#### Mil-std (military Standard):

Mil-g-45204 spec.