NSN 5935-01-248-5909

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-248-5909

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape w/screw locks
Overall Length:
0.785 inches
Overall Height:
0.735 inches
Overall Width:
0.308 inches
Environmental Protection:
Thermal shock resistant and shock resistant and vibration resistant and moisture resistant and salt water resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
9 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:

Mil-g-45204, type 2, cl 1, gr c military specification single treatment response single mating end single contact grouping

Contact Surface Treatment Specification:

Plastic diallyl phthalate single mating end and glass fiber single mating end or plastic polyester single mating end

NSN 5935-01-248-5909

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Plug Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy or aluminum alloy 6061
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Shell Material Specification:
Qq-a-591 federal specification single material response or qq-a-200 federal specification single material response
Insert Material Specification:
Mil-m-14, ty sdg-f military specification 1st material response single mating end and mil-m-14, ty sdg-f military specification 2nd material
response single mating end or mil-m-24519 military specification single material response single mating end
Included Contact Quantity:
9 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.009 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0