Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-248-7102

Thread Class:	
2b	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape, internal coupling w/strain relief	
Body Length:	
4.035 inches	
Overall Diameter:	
1.588 inches	
Environmental Protection:	
Explosion proof and corrosion resistant and vibration resistant and shock res	istant
Cable Entrance Diameter:	
0.750 inches	
Threaded Device Type:	
Coupling facility	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
22-27 single mating end	
Contact Removability:	
Removable single mating end all contact groupings	
Contact Maximum Current Rating In Amps:	
46.0 single mating end 1st contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
900.0 single mating end 1st contact grouping	
Contact Maximum Dc Voltage Rating In Volts:	
700.0 single mating end 2nd contact grouping	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
0.0	
Shell Type:	
Solid	
Connector Locking Method:	
Internally threaded coupling ring	
Connector Cable Strain Relief Method:	
Cable clamp	
Thready Qty Per Inch (tpi):	
18	
Thread Size:	
1.375 inches	

## NSN 5935-01-248-7102

Electrical Plug Connector - Page 2 of 2



**Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Silver single mating end 1st contact groupinggold single mating end 2nd contact grouping and nickel single mating end 2nd contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end all contact groupings Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate Shell Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification all treatment responses **Included Contact Quantity:** 8 single mating end 2nd contact grouping **Included Contact Type:** Round socket single mating end all contact groupings **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.008 gold grains, troy and 0.005 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0