

View Online at <https://aerobasegroup.com/nsn/5935-01-248-8420>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, rectangular

**Overall Length:**

3.310 inches

**Overall Height:**

0.870 inches

**Overall Width:**

2.000 inches

**Environmental Protection:**

Corrosion resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.125 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.468 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.688 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Connector Locking Method:**

Jackscrew

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end and glass fiber single mating end or plastic polyester single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, gr c, cl 1 military specification 1st treatment response single mating end single contact grouping

**Terminal Type:**

Wire wrap single mating end single contact grouping

**Contact Material Specification:**

Qq-b-750 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, ty sdg-f, ty gdi-30f military specification 1st material response single mating end and mil-m-14, ty sdg-f, ty gdi-30f military specification 2nd material response single mating end or mil-m-24519 military specification single material response single mating end

**Included Contact Quantity:**

75 single mating end single contact grouping

**Included Contact Type:**

Hermaphrodite single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.075 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-28731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Specification Data:**

81349-mil-c-28731/29 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.