NSN 5935-01-248-8420

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-248-8420 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, rectangular **Overall Length:** 3.310 inches **Overall Height:** 0.870 inches **Overall Width:** 2.000 inches **Environmental Protection:** Corrosion resistant and thermal shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.468 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.688 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Jackscrew Thready Qty Per Inch (tpi): **Thread Size:**

32

0.138 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

NSN 5935-01-248-8420

Electrical Receptacle Connector - Page 2 of 2



Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end or plastic polyester single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, gr c, cl 1 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Wire wrap single mating end single contact grouping

Contact Material Specification:

Qq-b-750 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f, ty gdi-30f military specification 1st material response single mating end and mil-m-14, ty sdg-f, ty gdi-30f military specification 2nd material response single mating end or mil-m-24519 military specification single material response single mating end

Included Contact Quantity:

75 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.075 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-28731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-28731/29 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.