NSN 5935-01-248-9314

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-248-9314 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.490 inches **Overall Height:** 1.343 inches **Overall Width:** 1.343 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and vibration proof **Unthreaded Mounting Hole Diameter:** 0.120 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches **Distance From Mounting Shoulder To Front Face:** Between 0.708 inches and 0.728 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 18-31 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Thread Length:** 0.290 inches Thready Qty Per Inch (tpi):

18

NSN 5935-01-248-9314

Electrical Receptacle Connector - Page 2 of 3



Thread Size:	
1.062 inches	
Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping	
Insert Material:	
Plastic epoxy single mating end	
Contact Surface Treatment Specification:	
Mil-g-45204, type 1, class 2 military specification single treatment response single mating end single contact grouping	
Terminal Type:	
Crimp single mating end single contact grouping	
Shell Material:	
Aluminum alloy	
Shell Surface Treatment:	
Cadmium	
Shell Surface Treatment Specification:	
Qq-p-416 federal specification single treatment response	
Shell Material Specification:	
Qq-a-367 federal specification single material response	
Included Contact Quantity:	
31 single mating end single contact grouping	
Included Contact Type:	
Round pin single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.031 gold grains, troy	
Precious Material:	
Gold	
Test Data Document:	
81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in sp	cification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on cer	tain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Thread Series Designator:	
Unef	
Specification Data:	
81349-mil-c-83723/72 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	

Demilitarization:

NSN 5935-01-248-9314

Electrical Receptacle Connector - Page 3 of 3



Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.