

View Online at <https://aerobasegroup.com/nsn/5935-01-248-9772>

Body Style:

Wall type

Overall Width:

1.750 inches

Body Length:

2.875 inches

Environmental Protection:

Vibration resistant and shock resistant and corrosion resistant

Distance Between Mounting Facility Centers:

3.281 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

"3, 5-15" single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

15.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

125.0 single mating end all contact groupings

Polarization Method:

Mating end

Connector Locking Method:

Friction

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper single mating end all contact groupings or copper alloy single mating end all contact groupings

Terminal Type:

Screw single mating end all contact groupings

Included Contact Quantity:

2 single mating end 2nd contact grouping

Included Contact Type:

Flat socket single mating end 2nd contact grouping

Test Data Document:

81349-mil-r-2726 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-2726/71 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0