

View Online at <https://aerobasegroup.com/nsn/5935-01-248-9772>

**Body Style:**

Wall type

**Overall Width:**

1.750 inches

**Body Length:**

2.875 inches

**Environmental Protection:**

Vibration resistant and shock resistant and corrosion resistant

**Distance Between Mounting Facility Centers:**

3.281 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

"3, 5-15" single mating end

**Contact Removability:**

Removable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

15.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

125.0 single mating end all contact groupings

**Polarization Method:**

Mating end

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper single mating end all contact groupings or copper alloy single mating end all contact groupings

**Terminal Type:**

Screw single mating end all contact groupings

**Included Contact Quantity:**

2 single mating end 2nd contact grouping

**Included Contact Type:**

Flat socket single mating end 2nd contact grouping

**Test Data Document:**

81349-mil-r-2726 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-r-2726/71 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0